







Longse DVR Price List for Distributor



Ver.: 201310A


H.264 4CH DVR

Model No.	<50PCS USD/SET	≥50PCS USD/SET	Specification	Products Show
LS-9604PD	\$26.8	\$26.8	Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out	  <p>4CH 960H</p> <p>960H*4CH, Network VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 2CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support:	
			CIF: 352×240 with 120 Fps (NTSC); 352×288 with 100 Fps (PAL)	
			D1: 720×480 with 120 Fps (NTSC); 704×576 with 100 Fps (PAL)	
			960H: 960×480 with 120 Fps (NTSC); 960×576 with 100 Fps (PAL)	
			Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL);	
			Playback resolution: 960H x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software	
			2×USB	
			1 SATA Hard Disk interface (2.5'/3.5' SATA,Up to 4TB)	
LS-9604PK	\$26.8	\$26.8	Backup: USB2.0 and Network	  <p>4CH 960H</p> <p>960H*4CH, Network VGA, USB Backup, USB Mouse</p>
			Support remote view by Mobilephone	
			Standard Color: White Optional Color: Black (Model LS-9604PDB)	
			Dimensions (L×W×H): 215*215*53(mm) weight: 2kg	
			Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out	
			Audio Input/Output: RCA 2CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support:	
			CIF: 352×240 with 120 Fps (NTSC); 352×288 with 100 Fps (PAL)	
			D1: 720×480 with 120 Fps (NTSC); 704×576 with 100 Fps (PAL)	
			960H: 960×480 with 120 Fps (NTSC); 960×576 with 100 Fps (PAL)	
			Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL);	
			Playback resolution: 960H x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
LS-9604U	\$38	\$36	1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software	 <p>4CH 960H</p> <p>960H*4CH, RS485, PTZ, Network HDMI,VGA, USB Backup, USB Mouse</p>
			2 × USB	
			1 SATA Hard Disk interface (2.5'/3.5' SATA,Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Standard Color: White Optional Color: Black (Model LS-9604PKB)	
			Dimensions (L×W×H): 206*206*51 (mm) weight: 2kg	
			Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out, HDMI 1CH Out	
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support:	
			CIF: 352×240 with 120 Fps (NTSC); 352×288 with 100 Fps (PAL)	
			D1: 720×480 with 120 Fps (NTSC); 704×576 with 100 Fps (PAL)	
			960H: 960×480 with 120 Fps (NTSC); 960×576 with 100 Fps (PAL)	
			Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL);	
			Playback resolution: 960H x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software	
			PTZ, RS485 x 1, 2 × USB, 1 × IR Controller	
			1 SATA Hard Disk interface (Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 354×245mm×45mm, weight: 4.0kg	





Model No.	<50PCS USD/SET	≥50PCS USD/SET	Specification	Products Show
LS-9604K	\$38	\$36	Video Input/Output: BNC 4CH In/ 1CH Out/ VGA 1CH Out, HDMI 1CH Out	 <p>4CH 960H</p> <p>960H*4CH, RS485, PTZ, Network HDMI,VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF: 352×240 with 120 Fps (NTSC); 352×288 with 100 Fps (PAL) D1: 720×480 with 120 Fps (NTSC); 704×576 with 100 Fps (PAL) 960H: 960×480 with 120 Fps (NTSC); 960×576 with 100 Fps (PAL)	
			Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL); Playback resolution: 960H x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software	
			PTZ, RS485 x 1, 2 × USB, 1 × IR Controller	
			1 SATA Hard Disk interface (Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 354×245mm×45mm, weight: 4.0kg	




HD-SDI 4CH DVR


Model No.	<50PCS USD/SET	≥50PCS USD/SET	Specification	Products Show
HD-3104E	\$139	\$133	Video Input/Output: BNC 4CH In / 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>4CH SDI</p> <p>1080P*4CH, RS485, Alarm, PTZ, Alarm, Network 2 SATA HD, HDMI, VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Alarm Input/Output: Alarm 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: 1920x1080 with 120 Fps (NTSC); 1920x1080 with 100 Fps (PAL)	
			Preview resolution: 1920x1080(NTSC), 1920x1080 (PAL); Playback resolution: 4x1080P	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software	
			PTZ, RS485, Alarm, 2×USB, 1×IR Controller	
			2 SATA Hard Disk interface (Up to 8TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 405mm×330mm×65mm, weight: 6.0kg	
HD-3104D	\$139	\$133	Video Input/Output: BNC 4CH In / 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>4CH SDI</p> <p>1080P*4CH, RS485, Alarm, PTZ, Alarm, Network 2 SATA HD, HDMI, VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Alarm Input/Output: Alarm 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: 1920x1080 with 120 Fps (NTSC); 1920x1080 with 100 Fps (PAL)	
			Preview resolution: 1920x1080(NTSC), 1920x1080 (PAL); Playback resolution: 4x1080P	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software	
			PTZ, RS485, Alarm, 2×USB, 1×IR Controller	
			2 SATA Hard Disk interface (Up to 8TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 405mm×325mm×65mm, weight: 6.0kg	

Model No.	<50PCS USD/SET	≥50PCS USD/SET	Specification	Products Show
HD-3104H	\$139	\$133	Video Input/Output: BNC 4CH In / 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>4CH SDI</p> <p>1080P*4CH, RS485, Alarm, PTZ, Alarm, Network 2 SATA HD, HDMI, VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Alarm Input/Output: Alarm 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: 1920x1080 with 120 Fps (NTSC); 1920x1080 with 100 Fps (PAL)	
			Preview resolution: 1920x1080(NTSC), 1920x1080 (PAL); Playback resolution: 4x1080P	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software	
			PTZ, RS485, Alarm, 2xUSB, 1xIR Controller	
			2 SATA Hard Disk interface (Up to 8TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 405mm×325mm×65mm, weight: 6.0kg	


H.264 8CH DVR


Model No.	<50PCS USD/SET	≥50PCS USD/SET	Specification	Products Show
LS-9508PD	\$35	\$33	Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out	  <p>NEW</p> <p>8CH Full D1</p> <p>D1*8CH, Network VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 2CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 240 Fps (NTSC); 352×288 with 200 Fps (PAL) D1:720×480 with 240 Fps (NTSC); 704×576 with 200 Fps (PAL)	
			Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL); Playback resolution: D1 x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software	
			2 × USB	
			1 SATA Hard Disk interface (2.5'/3.5' SATA, Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Standard Color: White Optional Color: Black (Model LS-9508PDB)	
			Dimensions (L×W×H): 215*215*53(mm) weight: 2kg	
LS-9508PK	\$35	\$33	Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out	  <p>NEW</p> <p>8CH Full D1</p> <p>D1*8CH, Network VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 2CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 240 Fps (NTSC); 352×288 with 200 Fps (PAL) D1:720×480 with 240 Fps (NTSC); 704×576 with 200 Fps (PAL)	
			Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL); Playback resolution: D1 x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software	
			2 × USB	
			1 SATA Hard Disk interface (2.5'/3.5' SATA, Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Standard Color: White Optional Color: Black (Model LS-9508PKB)	
			Dimensions (L×W×H): 206*206*51 (mm) weight: 2kg	


Model No.	<50PCS USD/SET	≥50PCS USD/SET	Specification	Products Show
LS-9508U	\$48	\$46	Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>8CH Full D1</p> <p>D1*8CH, RS485, PTZ, Network HDMI,VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 240 Fps (NTSC); 352×288 with 200 Fps (PAL) D1:720×480 with 240 Fps (NTSC); 704×576 with 200 Fps (PAL)	
			Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: D1 x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software	
			PTZ, RS485 x 1, 2 × USB, 1 × IR Controller	
			1 SATA Hard Disk interface (Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 354×245mm×45mm, weight: 4.0kg	
LS-9508K	\$48	\$46	Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>8CH Full D1</p> <p>D1*8CH, RS485, PTZ, Network HDMI,VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 240 Fps (NTSC); 352×288 with 200 Fps (PAL) D1:720×480 with 240 Fps (NTSC); 704×576 with 200 Fps (PAL)	
			Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: D1 x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software	
			PTZ, RS485 x 1, 2 × USB, 1 × IR Controller	
			1 SATA Hard Disk interface (Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 354×245mm×45mm, weight: 4.0kg	
LS-9608U	\$73	\$69	Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>8CH 960H</p> <p>960H*8CH, RS485, Alarm, PTZ, Network HDMI,VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Alarm Input/Output: Alarm 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 240 Fps (NTSC); 352×288 with 200 Fps (PAL) D1:720×480 with 240 Fps (NTSC); 704×576 with 200 Fps (PAL) 960H:960×480 with 240 Fps (NTSC); 960×576 with 200 Fps (PAL)	
			Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: 960H x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software	
			PTZ, RS485 x 1, 2 × USB, 1 × IR Controller	
			1 SATA Hard Disk interface (Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 354×245mm×45mm, weight: 4.0kg	


Model No.	<50PCS USD/SET	≥50PCS USD/SET	Specification	Products Show
LS-9608K	\$73	\$69	Video Input/Output: BNC 8CH In/ 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>8CH 960H</p> <p>960H*8CH, RS485, Alarm, PTZ, Network HDMI,VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Alarm Input/Output: Alarm 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 240 Fps (NTSC); 352×288 with 200 Fps (PAL) D1:720×480 with 240 Fps (NTSC); 704×576 with 200 Fps (PAL) 960H:960×480 with 240 Fps (NTSC); 960×576 with 200 Fps (PAL)	
			Preview resolution: 960 x 480 (NTSC), 960x 576 (PAL); Playback resolution: 960H x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS , Support Internet Explorer and special client software	
			PTZ, RS485 x 1, 2 × USB, 1 × IR Controller	
			1 SATA Hard Disk interface (Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 354×245mm×45mm, weight: 4.0kg	


H.264 16CH DVR

Model No.	<50PCS USD/SET	≥50PCS USD/SET	Specification	Products Show
LS-9516U	\$79	\$75	Video Input/Output: BNC 16CH In / 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>HOT</p> <p>16CH Full D1</p> <p>D1*16CH, RS485, Alarm, PTZ, Network HDMI,VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Alarm Input/Output: Alarm 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 480 Fps (NTSC); 352×288 with 400 Fps (PAL) D1:720×480 with 480 Fps (NTSC); 704×576 with 400 Fps (PAL)	
			Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: D1 x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software	
			PTZ, RS485x1, 2×USB, 1×IR Controller	
			1 SATA Hard Disk interface (Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 354×245mm×45mm, weight: 4.0kg	

LS-9516K	\$79	\$75	Video Input/Output: BNC 16CH In / 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>HOT</p> <p>16CH Full D1</p> <p>D1*16CH, RS485, Alarm, PTZ, Network HDMI,VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 4CH In/ 1CH Out	
			Alarm Input/Output: Alarm 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 480 Fps (NTSC); 352×288 with 400 Fps (PAL) D1:720×480 with 480 Fps (NTSC); 704×576 with 400 Fps (PAL)	
			Preview resolution: 720 x 480 (NTSC), 704 x 576 (PAL) ; Playback resolution: D1 x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software	
			PTZ, RS485x1, 2×USB, 1×IR Controller	
			1 SATA Hard Disk interface (Up to 4TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 354×245mm×45mm, weight: 4.0kg	

Model No.	<50PCS USD/SET	≥50PCS USD/SET	Specification	Products Show
LS-3116E	\$113	\$109	Video Input/Output: BNC 16CH In / 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>HOT</p> <p>16CH 960H</p> <p>960H*16CH, RS485, Alarm, PTZ, Alarm, Network 2 SATA HD, HDMI, VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 16CH In/ 1CH Out	
			Alarm Input/Output: Alarm 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 480 Fps (NTSC); 352×288 with 400 Fps (PAL) D1:720×480 with 480 Fps (NTSC); 704×576 with 400 Fps (PAL) 960H·960×480 with 480 Fps (NTSC)·960×576 with 400 Fps (PAL)	
			Preview resolution: 960 x 480 (NTSC), 960x 576 (PAL); Playback resolution: 960H x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software	
			Remote Control, PTZ, RS485, Alarm, 2×USB, 1×IR Controller	
			2 SATA Hard Disk interface (Up to 8TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 405mm×330mm×65mm, weight: 6.0kg	

LS-3116D	\$113	\$109	Video Input/Output: BNC 16CH In / 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>HOT</p> <p>16CH 960H</p> <p>960H*16CH, RS485, Alarm, PTZ, Alarm, Network 2 SATA HD, HDMI, VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 16CH In/ 1CH Out	
			Alarm Input/Output: Alarm 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 480 Fps (NTSC); 352×288 with 400 Fps (PAL) D1:720×480 with 480 Fps (NTSC); 704×576 with 400 Fps (PAL) 960H:960×480 with 480 Fps (NTSC); 960×576 with 400 Fps (PAL)	
			Preview resolution: 960 x 480 (NTSC), 960 x 576 (PAL); Playback resolution: 960H x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software	
			Remote Control, PTZ, RS485, Alarm, 2×USB, 1×IR Controller	
			2 SATA Hard Disk interface (Up to 8TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 405mm×325mm×65mm, weight: 6.0kg	

LS-3116H	\$113	\$109	Video Input/Output: BNC 16CH In / 1CH Out, VGA 1CH Out, HDMI 1CH Out	 <p>HOT</p> <p>16CH 960H</p> <p>960H*16CH, RS485, Alarm, PTZ, Alarm, Network 2 SATA HD, HDMI, VGA, USB Backup, USB Mouse</p>
			Audio Input/Output: RCA 16CH In/ 1CH Out	
			Alarm Input/Output: Alarm 4CH In/ 1CH Out	
			Compression Method: H.264	
			Real time recording support: CIF:352×240 with 480 Fps (NTSC); 352×288 with 400 Fps (PAL) D1:720×480 with 480 Fps (NTSC); 704×576 with 400 Fps (PAL) 960H:960×480 with 480 Fps (NTSC); 960×576 with 400 Fps (PAL)	
			Preview resolution:960 x 480 (NTSC), 960 x 576 (PAL); Playback resolution: 960H x 4	
			Hexaplex operation simultaneously: Preview, recording, playback, and network live, backup, playback	
			1 RJ-45 Ethernet connector, Static, Dynamic IP and DDNS, Support Internet Explorer and special client software	
			Remote Control, PTZ, RS485, Alarm, 2×USB, 1×IR Controller	
			2 SATA Hard Disk interface (Up to 8TB)	
			Backup: USB2.0 and Network	
			Support remote view by Mobilephone	
			Dimensions (L×W×H): 405mm×325mm×65mm, weight: 6.0kg	

Price Terms:	Say US\$, EX-Works Guangzhou
Terms of payment:	T/T, L/C, Paypal, West Union
Warranty:	Two Years after shipment date
Attention:	The Unit price fluctuates according to the change of parameters and market. And the price above is not including the delivery charge and other expenses