

Longse HD-IP Camera Price List for Distributor







Entry Date:2014.2.12

Ver.: V201402C

※ Promotion HD-IP Camera





| Product Show | Chief Characteristics | Model No. | Solution | Specification | <100pcs USD/SE | ≥100pcs USD/SE |
|--|--|-------------|-------------------|--|-------------------|-------------------|
|  | HOT IR LED: ϕ 5X24PCS IR range: 20M Board Lens 3.6mm/F2.0 Water resistance: IP66 3-Axis cable built-in bracket Size: 148(W) x 65(H) x 63(D)mm Weight: 500g | LBH24S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$29.80 | \$29.80 |
| | | LBH24T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$34.80 | \$34.80 |
| | | LBH24S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$32.80 | \$32.80 |
| | | LBH24T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$39.80 | \$39.80 |
| | | LBH24T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$51.80 | \$51.80 |
|  | Vandalproof IR Dome Camera IR LED: ϕ 5X24PCS IR range: 20M Board Lens 3.6mm/F2.0 Size: ϕ 94 x 69(H) mm Weight: 450g | LIRDNS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$27.80 | \$27.80 |
| | | LIRDNS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$30.80 | \$30.80 |
|  | HOT Vandalproof IR Dome Camera IR LED: ϕ 5X48PCS IR range: 30M Board Lens 6mm/F2.0 Size: ϕ 131 x 93(H) mm Weight: 800g With Deep Base add USD3 | LIRDN48S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$31.80 | \$31.80 |
| | | LIRDN48T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$36.80 | \$36.80 |
| | | LIRDN48S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$34.80 | \$34.80 |
| | | LIRDN48T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$41.80 | \$41.80 |
| | | LIRDN48T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$53.80 | \$53.80 |
|  | 3 Axis Plastic Dome Camera Board Lens 3.6mm/F2.0 Size: ϕ 117x 80(H) mm Weight: 500g | LPDS35S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens | \$21.80 | \$21.80 |
| | | LPDS35S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens | \$24.80 | \$24.80 |



| | | | | | | |
|--|--|------------|-------------------|---|---------|---------|
|   | 3 Axis Plastic Dome Camera 2.8 12mm Manual Zoom Lens Size: \varnothing 138x 94(H) mm Weight: 700g | LPDS45S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens | \$32.80 | \$32.80 |
| | | LPDS45T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens | \$37.80 | \$37.80 |
| | | LPDS45S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens | \$35.80 | \$35.80 |
| | | LPDS45T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens | \$42.80 | \$42.80 |
| | | LPDS45T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens | \$54.80 | \$54.80 |
|  | IR LED: \varnothing 5X30PCS IR range: 25M Board Lens 3.6mm/F2.0 Water resistance: IP66 3-Axis cable built-in bracket Size: 200(W) x 82(H) x 75(D)mm Weight: 880g | LIW30S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT <u>External POE + 8USD</u> | \$32.80 | \$32.80 |
| | | LIW30T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT <u>External POE + 8USD</u> | \$37.80 | \$37.80 |
| | | LIW30S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT <u>External POE + 8USD</u> | \$35.80 | \$35.80 |
| | | LIW30T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT <u>External POE + 8USD</u> | \$42.80 | \$42.80 |
| | | LIW30T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT <u>External POE + 8USD</u> | \$54.80 | \$54.80 |
|  | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 291(W) x 90(H) x 93(D)mm Weight: 1.6KG | LIG40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT <u>Built-in/External POE + 4/8USD</u> | \$42.80 | \$42.80 |
| | | LIG40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT <u>Built-in/External POE + 4/8USD</u> | \$47.80 | \$47.80 |
| | | LIG40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT <u>Built-in/External POE + 4/8USD</u> | \$45.80 | \$45.80 |
| | | LIG40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT <u>Built-in/External POE + 4/8USD</u> | \$52.80 | \$52.80 |
| | | LIG40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT <u>Built-in/External POE + 4/8USD</u> | \$64.80 | \$64.80 |
|   | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 220(W) x 80(H) x 80(D)mm Weight: 1.4KG | LID40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT <u>Built-in/External POE + 4/8USD</u> | \$43.80 | \$43.80 |
| | | LID40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT <u>Built-in/External POE + 4/8USD</u> | \$48.80 | \$48.80 |
| | | LID40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT <u>Built-in/External POE + 4/8USD</u> | \$46.80 | \$46.80 |
| | | LID40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT <u>Built-in/External POE + 4/8USD</u> | \$53.80 | \$53.80 |
| | | LID40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT <u>Built-in/External POE + 4/8USD</u> | \$65.80 | \$65.80 |



| | | | | | | |
|---|--|------------|-------------------|--|---------|---------|
|   | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 260(W) x 98(H) x 95(D)mm Weight: 1.7KG | LID90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$47.80 | \$47.80 |
| | | LID90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52.80 | \$52.80 |
| | | LID90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50.80 | \$50.80 |
| | | LID90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$57.80 | \$57.80 |
| | | LID90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$69.80 | \$69.80 |
|   | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 220(W) x 80(H) x 80(D)mm Weight: 1.4KG | LIV40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$42.80 | \$42.80 |
| | | LIV40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$47.80 | \$47.80 |
| | | LIV40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$45.80 | \$45.80 |
| | | LIV40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52.80 | \$52.80 |
| | | LIV40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$64.80 | \$64.80 |
|   | IR LED: \varnothing 5X42PCS IR range: 40M 2.8 - 12mm Manual Zoom Lens Water resistance: IP66 DC12V/AC24V double voltage add USD4 Size: 200(W) x 171(H) x 83(D)mm Weight: 1.4Kg | LIA40ES100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$42.80 | \$42.80 |
| | | LIA40ET100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$47.80 | \$47.80 |
| | | LIA40ES130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$45.80 | \$45.80 |
| | | LIA40ET130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52.80 | \$52.80 |
| | | LIA40ET200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$64.80 | \$64.80 |



HD-IP Fixed Lens Dome Camera


| | | | | | | |
|---|--|------------|-------------------|--|------|------|
|   | Vandalproof IR Dome Camera IR LED: \varnothing 5X48PCS IR range: 40M Board Lens:6mm Size: \varnothing 131 x 93(H) mm Weight: 800g With Deep base add USD3 | LIRDS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$36 | \$34 |
| | | LIRDT100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$41 | \$39 |
| | | LIRDS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$39 | \$37 |
| | | LIRDT130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$46 | \$44 |
| | | LIRDT200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$52 | \$50 |
|  | Plastic Dome Camera Board Lens 3.6mm/F2.0 Size: \varnothing 108 x 60(H) mm Weight: 300g | LCDFS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens | \$28 | \$26 |
| | | LCDFS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens | \$31 | \$29 |
|  | Plastic IR Dome Camera IR LED: \varnothing 5X24PCS IR range: 20M Board Lens 3.6mm/F2.0 Size: \varnothing 94 x 69(H) mm Weight: 300g | LIRDPS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT | \$28 | \$26 |
| | | LIRDPS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT | \$31 | \$29 |
|  | Vandalproof IR Dome Camera IR LED: \varnothing 5X24PCS IR range: 20M Board Lens 3.6mm/F2.0 Size: \varnothing 94 x 69(H) mm Weight: 400g | LIRDBS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$32 | \$30 |
| | | LIRDBS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$35 | \$33 |
|  | Vandalproof IR Dome Camera IR LED: \varnothing 5X24PCS IR range: 20M Board Lens 3.6mm/F2.0 Size: \varnothing 89 x 76(H) mm Weight:450g | LIRDGS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$32 | \$30 |
| | | LIRDGS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$35 | \$33 |
|  | 3-Axis Vandalproof Dome Camera Board Lens 3.6mm/F2.0 Size: \varnothing 94x 85(H) mm Weight: 650g | LVDN25S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$32 | \$30 |
| | | LVDN25S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$35 | \$33 |


| HD-IP Varifocal Lens Dome Camera | | | | | | |
|---|---|-------------|-------------------|---|-------------------|-------------------|
| Product Show | Chief Characteristics | Model No. | Solution | Specification | <100pcs USD/SE | ≥100pcs USD/SE |
|  | 3 Axis Plastic Dome Camera 2.8 12mm Manual Zoom Lens Size: \varnothing 128 x 98.5(H) mm Weight: 750g | LCDNTS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$37 | \$35 |
| | | LCDNTS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$40 | \$38 |
|  | 3 Axis Plastic Dome Camera IR LED: \varnothing 5X21PCS IR range: 20M 2.8-12mm Manual Zoom Lens Size: \varnothing 128 x 98.5(H) mm Weight: 750g | LCDNT20S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$38 | \$36 |
| | | LCDNT20T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$43 | \$41 |
| | | LCDNT20S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$41 | \$39 |
| | | LCDNT20T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$48 | \$46 |
| | | LCDNT20T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$62 | \$60 |
|  | 3 Axis Plastic Dome Camera IR LED: \varnothing 5X21PCS IR range: 20M 2.8-12mm Manual Zoom Lens Size: \varnothing 135 x 100(H) mm Weight: 650g | LCDNB20S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$39 | \$37 |
| | | LCDNB20T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$44 | \$42 |
| | | LCDNB20S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$42 | \$40 |
| | | LCDNB20T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$49 | \$47 |
| | | LCDNB20T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$63 | \$61 |
| <div>New</div>  | 3 Axis Vandalproof & Waterproof Dome Camera Water resistance: IP66 2.8 12mm Manual Zoom Lens Size: \varnothing 148×111(H)mm Weight: 1.2KG With Bracket add USD6 | LVWDBS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$53 | \$51 |
| | | LVWDBT100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$58 | \$56 |
| | | LVWDBS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LVWDBT130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$63 | \$61 |
| | | LVWDBT200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$77 | \$75 |


| | | | | | | |
|--|--|-------------|-------------------|--|------|------|
|   | 3 Axis Vandalproof & Waterproof Dome Camera Water resistance: IP66 IR LED: \varnothing 5X21PCS IR range: 20M 2.8-12mm Manual Zoom Lens Size: \varnothing 148 \times 111(H)mm Weight: 1.2KG With Bracket add USD6 | LVWDB20S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$55 | \$53 |
| | | LVWDB20T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$60 | \$58 |
| | | LVWDB20S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$58 | \$56 |
| | | LVWDB20T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$65 | \$63 |
| | | LVWDB20T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$79 | \$77 |


| | | | | | | |
|--|---|-----------|-------------------|--|------|------|
|   | 3 Axis Vandalproof & Waterproof Dome Camera Water resistance: IP66 2.8 12mm Manual Zoom Lens Size: \varnothing 151 \times 108(H)mm Weight: 1.2KG With Bracket add USD6 | LVWDCS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$53 | \$51 |
| | | LVWDCT100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$58 | \$56 |
| | | LVWDCS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LVWDCT130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$63 | \$61 |
| | | LVWDCT200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$77 | \$75 |


| | | | | | | |
|---|--|-------------|-------------------|--|------|------|
|   | 3 Axis Vandalproof & Waterproof Dome Camera Water resistance: IP66 IR LED: \varnothing 5X21PCS IR range: 20M 2.8-12mm Manual Zoom Lens Size: \varnothing 151 \times 108(H)mm Weight: 1.2KG With Bracket add USD6 | LVWDC20S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$55 | \$53 |
| | | LVWDC20T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$60 | \$58 |
| | | LVWDC20S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$58 | \$56 |
| | | LVWDC20T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$65 | \$63 |
| | | LVWDC20T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$79 | \$77 |

| | | | | | | |
|--|--|------------|-------------------|--|------|------|
|  | 3 Axis Vandalproof Dome Camera IR LED: \varnothing 5X21PCS IR range: 20M 2.8-12mm Manual Zoom Lens Size: \varnothing 145x 95(H) mm Weight: 1.2kg | LVDL45S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$47 | \$45 |
| | | LVDL45T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$52 | \$50 |
| | | LVDL45S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LVDL45T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$57 | \$55 |
| | | LVDL45T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$71 | \$69 |



| | | | | | | |
|--|--|------------|-------------------|--|------|------|
|  | 3 Axis Vandalproof Dome Camera IR LED: \varnothing 5X30PCS IR range: 25M 2.8-12mm Manual Zoom Lens Size: \varnothing 136x 95(H) mm Weight: 1.1kg | LVDM45S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$47 | \$45 |
| | | LVDM45T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$52 | \$50 |
| | | LVDM45S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LVDM45T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$52 | \$55 |
| | | LVDM45T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$71 | \$69 |

| | | | | | | |
|--|--|------------|-------------------|--|------|------|
|  | 3 Axis Vandalproof Dome Camera IR LED: \varnothing 5X30PCS IR range: 25M 2.8-12mm Manual Zoom Lens DC12V/AC24V double voltage add USD4 (except LVDT45SE) Size: \varnothing 158 x 118(H) mm Weight: 1.3kg | LVDT45S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LVDT45T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$54 | \$52 |
| | | LVDT45S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LVDT45T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$59 | \$57 |
| | | LVDT45T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$73 | \$71 |


| | | | | | | |
|--|---|------------|-------------------|--|------|------|
|  | 3 Axis Vandalproof Dome Camera IR LED: Ø 5X30PCS IR range: 25M 2.8-12mm Manual Zoom Lens Size: Ø 135 x 110(H) mm Weight: 1.2kg With bracket add USD5 | LVDC45S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LVDC45T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$54 | \$52 |
| | | LVDC45S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LVDC45T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$59 | \$57 |
| | | LVDC45T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$73 | \$71 |


| | | | | | | |
|---|---|------------|-------------------|--|------|------|
|  | 3 Axis Vandalproof Dome Camera IR LED: Ø 5X30PCS IR range: 25M 2.8-12mm Manual Zoom Lens Size: Ø 140 x 110(H) mm Weight: 1.2kg With bracket add USD5 | LVDF45S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LVDF45T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$54 | \$52 |
| | | LVDF45S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LVDF45T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$59 | \$57 |
| | | LVDF45T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$73 | \$71 |


HD-IP Fixed Lens Weatherproof IR Camera


| Product Show | Chief Characteristics | Model No. | Solution | Specification | <100pcs USD/SE | ≥100pcs USD/SE |
|--|---|-----------|-------------------|--|-------------------|-------------------|
|  |  IR LED: Ø 5X36PCS IR range: 30M Board Lens 3.6mm/F2.0 Water resistance: IP66 3-Axis cable built-in bracket Size: 177(W) x 76(H) x 74(D)mm Weight: 700g | LBH36S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$37 | \$35 |
| | | LBH36T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$42 | \$40 |
| | | LBH36S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$40 | \$38 |
| | | LBH36T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$47 | \$45 |
| | | LBH36T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$61 | \$59 |


| | | | | | | |
|---|---|------------|-------------------|--|------|------|
|   | IR LED: \varnothing 5X48PCS IR range: 40M Board Lens 3.6mm/F2.0 Water resistance: IP66 3-Axis cable built-in bracket Size: 177(W) x 76(H) x 74(D)mm Weight: 700g | LBH48S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$38 | \$36 |
| | | LBH48T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$43 | \$41 |
| | | LBH48S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$41 | \$39 |
| | | LBH48T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$48 | \$46 |
| | | LBH48T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$62 | \$60 |
|   | IR LED: \varnothing 5X30PCS IR range:25M Board Lens 3.6mm/F2.0 Water resistance:IP66 3-Axis cable built-in bracket Size: 196(W) x 89(H) x 75(D)mm Weight: 880g | LICG30S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$36 | \$34 |
| | | LICG30T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$41 | \$39 |
| | | LICG30S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$39 | \$37 |
| | | LICG30T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$46 | \$44 |
| | | LICG30T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$60 | \$58 |
|   | IR LED: \varnothing 5X36PCS IR range: 30M CS Lens 6mm/F2.0 Water resistance: IP66 3-Axis cable built-in bracket Size: 213(W) x 93(H) x 83(D)mm Weight: 880g | LICG36S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$37 | \$35 |
| | | LICG36T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$42 | \$40 |
| | | LICG36S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$40 | \$38 |
| | | LICG36T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$47 | \$45 |
| | | LICG36T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$61 | \$59 |


| | | | | | | |
|--|---|-----------|-------------------|--|------|------|
|  | IR LED: \varnothing 5X42PCS IR range: 40M CS Lens 6mm/F2.0 Water resistance: IP66 3-Axis cable built-in bracket Size: 228(W) x 97(H) x 82(D)mm Weight: 1.4Kg | LIK40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$39 | \$37 |
| | | LIK40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$44 | \$42 |
| | | LIK40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$42 | \$40 |
| | | LIK40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LIK40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$63 | \$61 |






| | | | | | | |
|--|--|------------|-------------------|--|------|------|
|  | IR LED: \varnothing 5X30PCS IR range: 25M Board Lens 3.6mm/F2.0 Water resistance: IP66 3-Axis cable built-in bracket Size: 200(W) x 70(H) x 65(D)mm Weight: 1.3kg | LIED30S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$41 | \$39 |
| | | LIED30T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$46 | \$44 |
| | | LIED30S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$44 | \$42 |
| | | LIED30T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIED30T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$65 | \$63 |







| | | | | | | |
|--|---|-----------|-------------------|--|------|------|
|  | IR LED: \varnothing 5X30PCS IR range: 25M Board Lens 3.6mm/F2.0 Water resistance: IP66 3-Axis cable built-in bracket Size: 190(W) x 167(H) x 83(D)mm Weight: 1.6kg | LIE30S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$41 | \$39 |
| | | LIE30T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$46 | \$44 |
| | | LIE30S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$44 | \$42 |
| | | LIE30T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIE30T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$65 | \$63 |







| | | | | | | |
|--|--|-----------|-------------------|--|------|------|
|  | IR LED: \varnothing 42X1PC IR rang:20M Board Lens 3.6mm/F2.0 Water Resistance:IP66 3-Axis cable built-in bracket Size:200(W) x 82(H) x 91(D)mm Weight:1.3kg | LBF20S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$39 | \$37 |
| | | LBF20T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$44 | \$42 |
| | | LBF20S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$42 | \$40 |
| | | LBF20T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LBF20T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$63 | \$61 |







| | | | | | | |
|---|---|-----------|-------------------|--|------|------|
|  | IR LED: \varnothing 42X2PCS IR range: 40M CS Lens 8mm/F2.0 Water resistance: IP66 Size: 212(W) x 93(H) x 110(D)mm Weight: 1.5Kg | LIF40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$43 | \$41 |
| | | LIF40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$48 | \$46 |
| | | LIF40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$46 | \$44 |
| | | LIF40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$53 | \$51 |
| | | LIF40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$67 | \$65 |



| | | | | | | |
|--|---|-----------|-------------------|--|------|------|
|  | IR LED: \varnothing 42X4PCS IR range: 80M CS Lens 12mm/F2.0 Water resistance: IP66 Size: 275(W) x 113(H) x 139(D)mm Weight: 2.0Kg | LIF80S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LIF80T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LIF80S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LIF80T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$59 | \$57 |
| | | LIF80T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$73 | \$71 |


| HD-IP Varifocal Lens Weatherproof IR Camera | | | | | | |
|---|--|-----------|-------------------|--|-------------------|-------------------|
| Product Show | Chief Characteristics | Model No. | Solution | Specification | <100pcs USD/SE | ≥100pcs USD/SE |
|   | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 305(W) x 113(H) x 103(D)mm Weight: 1.8KG | LIG90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LIG90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LIG90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LIG90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$59 | \$57 |
| | | LIG90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$73 | \$71 |
|   | IR LED: \varnothing 5X42PCS IR Range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 233(W) x 90(H) x 87.5(D)mm Weight: 1.4KG | LBA40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$45 | \$43 |
| | | LBA40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$50 | \$48 |
| | | LBA40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$48 | \$46 |
| | | LBA40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$55 | \$53 |
| | | LBA40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$69 | \$67 |
|   | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 255.8(W) x 98(H) x 95(D)mm Weight: 1.7KG | LBA90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LBA90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LBA90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LBA90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$59 | \$57 |
| | | LBA90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$73 | \$71 |


| | | | | | | |
|---|--|-----------|-------------------|---|------|------|
|   | IR LED: \varnothing 5X42PCS IR Range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 236.5(W) x 89(H) x 85.5(D)mm Weight: 1.4KG | LBB40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$45 | \$43 |
| | | LBB40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$50 | \$48 |
| | | LBB40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$48 | \$46 |
| | | LBB40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$55 | \$53 |
| | | LBB40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$69 | \$67 |
|   | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 255.8(W) x 98(H) x 95(D)mm Weight: 1.7KG | LBB90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LBB90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LBB90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LBB90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$59 | \$57 |
| | | LBB90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$73 | \$71 |
|   | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 242(W) x 84(H) x 86(D)mm Weight: 1.6KG | LIU40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$46 | \$44 |
| | | LIU40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$51 | \$49 |
| | | LIU40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LIU40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT External POE +8USD | \$56 | \$54 |
| | | LIU40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT External POE + 8USD | \$70 | \$68 |






| | | | | | | |
|---|--|-----------|-------------------|---|------|------|
|   | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 298(W) x 100(H) x 106(D)mm Weight: 1.7KG | LIU90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LIU90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$55 | \$53 |
| | | LIU90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$53 | \$51 |
| | | LIU90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$60 | \$58 |
| | | LIU90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$74 | \$72 |
|   | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 275(W) x 91(H) x 80(D)mm Weight: 1.4KG | LIN40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$48 | \$45 |
| | | LIN40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LIN40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LIN40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$57 | \$55 |
| | | LIN40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$71 | \$69 |
|   | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 312(W) x 133(H) x 102(D)mm Weight: 1.8KG | LIN90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIN90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LIN90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LIN90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$61 | \$59 |
| | | LIN90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$75 | \$73 |


| | | | | | | |
|---|---|------------|-------------------|---|------|------|
|   | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 220(W) x 80(H) x 80(D)mm Weight: 1.4KG | LIW40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$47 | \$45 |
| | | LIW40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LIW40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LIW40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$57 | \$55 |
| | | LIW40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$71 | \$69 |
|   | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 260(W) x 98(H) x 95(D)mm Weight: 1.7KG | LIW90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIW90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LIW90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LIW90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$61 | \$59 |
| | | LIW90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$75 | \$73 |
|   | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 290(W) x 92(H) x 80(D)mm Weight: 1.85KG | LIZM40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$40 | \$38 |
| | | LIZM40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$45 | \$43 |
| | | LIZM40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$43 | \$41 |
| | | LIZM40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LIZM40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$60 | \$58 |


| | | | | | | |
|---|---|------------|-------------------|--|------|------|
|   | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 315(W) x 120(H) x 100(D)mm Weight: 1.85KG | LIZM90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIZM90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LIZM90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LIZM90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$61 | \$59 |
| | | LIZM90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$75 | \$73 |


| | | | | | | |
|---|--|-----------|-------------------|--|------|------|
|  | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 220(W) x 80(H) x 80(D)mm Weight: 1.4KG | LIB40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$46 | \$44 |
| | | LIB40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIB40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LIB40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LIB40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$70 | \$68 |


| | | | | | | |
|--|--|-----------|-------------------|--|------|------|
|  | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 260(W) x 98(H) x 95(D)mm Weight: 1.7KG | LIB90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LIB90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$55 | \$53 |
| | | LIB90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$53 | \$51 |
| | | LIB90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$60 | \$58 |
| | | LIB90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$74 | \$72 |


| | | | | | | |
|--|---|-----------|-------------------|---|------|------|
|    | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 260(W) x 98(H) x 95(D)mm Weight: 1.7KG With Deep base add USD3 | LIV90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LIV90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LIV90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LIV90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$59 | \$57 |
| | | LIV90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$73 | \$71 |
|  | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 216(W) x 188(H) x 91(D)mm Weight: 1.6Kg | LIE40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$46 | \$44 |
| | | LIE40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIE40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LIE40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LIE40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$70 | \$68 |
|  | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 220(W) x 200(H) x 107(D)mm Weight: 1.8Kg | LIE90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LIE90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$55 | \$53 |
| | | LIE90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$53 | \$51 |
| | | LIE90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$60 | \$58 |
| | | LIE90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$74 | \$72 |


| | | | | | | |
|--|--|------------|-------------------|---|------|------|
|  | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 228(W) x 97(H) x 82(D)mm Weight: 1.4Kg | LIKT40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$46 | \$44 |
| | | LIKT40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIKT40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LIKT40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LIKT40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$70 | \$68 |


| | | | | | | |
|--|--|------------|-------------------|---|------|------|
|  | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket Size: 295(W) x 120(H) x 103(D)mm Weight: 1.7Kg | LIKT90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LIKT90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$55 | \$53 |
| | | LIKT90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$53 | \$51 |
| | | LIKT90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$60 | \$58 |
| | | LIKT90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$74 | \$72 |


| | | | | | | |
|--|---|------------|-------------------|---|------|------|
|  | IR LED: \varnothing 5X42PCS IR range: 40M 2.8-12mm Manual Zoom Lens 3-Axis Cable Build-in Bracket Water resistance: IP66 Size: 280(W) x 100(H) x 91(D)mm Weight: 1.6Kg | LIED40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$47 | \$45 |
| | | LIED40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LIED40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LIED40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$57 | \$55 |
| | | LIED40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$71 | \$69 |


| | | | | | | |
|--|--|-------------------|--------------------------|---|-------------|-------------|
|  | IR LED: \varnothing 5X72PCS IR range: 60M 2.8-12mm Manual Zoom Lens Water resistance: IP66 3-Axis cable built-in bracket DC12V/AC24V double voltage add USD4 Size: 318(W) x 110(H) x 107(D)mm Weight: 1.7Kg With Deep base add USD3 | LIED90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIED90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LIED90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LIED90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$61 | \$59 |
| | | LIED90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$75 | \$73 |

| | | | | | | |
|---|---|------------------|--------------------------|---|-------------|-------------|
|  | IR LED: \varnothing 5X42PCS IR range: 40M 2.8 - 12mm Manual Zoom Lens Water resistance: IP66 3 - Axis cable built - in bracket Size: 260(W) x 112(H) x 85(D)mm Weight: 1.4Kg | LIP40S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$47 | \$45 |
| | | LIP40T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LIP40S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LIP40T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$57 | \$55 |
| | | LIP40T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$71 | \$69 |

| | | | | | | |
|--|--|------------------|--------------------------|---|-------------|-------------|
|  | IR LED: \varnothing 5X72PCS IR range: 60M 2.8 - 12mm Manual Zoom Lens Water resistance: IP66 3 - Axis cable built - in bracket Size: 275(W) x 125(H) x 105(D)mm Weight: 1.7Kg | LIP90S100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIP90T100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LIP90S130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LIP90T130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$60 | \$59 |
| | | LIP90T200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$75 | \$73 |

| | | | | | | |
|--|--|------------|-------------------|---|------|------|
|  | IR LED: \varnothing 5X72PCS IR range: 60M 2.8 - 12mm Manual Zoom Lens Water resistance: IP66 DC12V/AC24V double voltage add USD4 Size: 240(W) x 186(H) x 100(D)mm Weight: 1.7Kg | LIA90ES100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LIA90ET100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$54 | \$52 |
| | | LIA90ES130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$52 | \$50 |
| | | LIA90ET130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$59 | \$57 |
| | | LIA90ET200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$73 | \$71 |

| | | | | | | |
|---|--|------------|-------------------|---|------|------|
|  | IR LED: \varnothing 5X42PCS IR range: 40M 2.8 - 12mm Manual Zoom Lens Water resistance: IP66 3 - Axis cable built - in bracket DC12V/AC24V double voltage add USD4 Size: 207(W) x 184(H) x 83(D)mm Weight: 1.4Kg | LIA40DS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$46 | \$44 |
| | | LIA40DT100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$51 | \$49 |
| | | LIA40DS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$49 | \$47 |
| | | LIA40DT130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$56 | \$54 |
| | | LIA40DT200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$70 | \$68 |

| | | | | | | |
|--|---|------------|-------------------|---|------|------|
|  | IR LED: \varnothing 5X72PCS IR range: 60M 2.8 - 12mm Manual Zoom Lens Water resistance: IP66 3 - Axis cable built - in bracket DC12V/AC24V double voltage add USD4 Size: 255(W) x 110(H) x 105(D)mm Weight: 1.7Kg | LIA90DS100 | OV9712S + Hi3518C | 1/4" OmniVision 1 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$50 | \$48 |
| | | LIA90DT100 | OV9712S + DM365 | 1/4" OmniVision 1 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 720P@25fps; 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$55 | \$53 |
| | | LIA90DS130 | IMX138 + Hi3518C | 1/3" SONY Low Illumination 1.3 Megapixel CMOS Sensor HISILICON DSP Hi3518C Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$53 | \$51 |
| | | LIA90DT130 | AR0130 + DM365 | 1/3" Aptina Low Illumination 1.3 Megapixel CMOS Sensor TI DaVinci™ DSP DM365 Main Stream: 960P@25fps, 720P@25fps 2 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$60 | \$58 |
| | | LIA90DT200 | IMX222 + DM368 | 1/3" SONY 2.4 Megapixel High-resolution CMOS Sensor TI DaVinci™ DSP DM368 Main Stream: 1080P@25fps, 720P@25fps 3 Megapixel HD Lens, with IR-CUT Built-in/External POE + 4/8USD | \$74 | \$72 |

| | |
|-------------------------|--|
| Price Terms: | Say US\$, EX-Works Guangzhou |
| Minimum Order Quantity: | 10pcs/model after sample order |
| Terms of payment: | T/T, L/C, Paypal, West Union |
| Warranty: | Two Years after shipment date |
| Attention: | The Unit price fluctuates according to the change of parameters and market. And the price above is not including the delivery charge and other expenses. |

On Line Demo:

LVDC45T130 <http://120.197.60.19:8072>

ID 1: longse Password: longse

LVDC45T200 <http://120.197.60.19:8071>

ID 1: longse Password: longse

Longse Factory Tour:

